

you can **RELY** on

CEMENTAID

www.cementaid.com

SPECIFICATION FOR

PENETRATING CONCRETE SEALER

CALRES 120

REQUIREMENT:

The protection of industrial concrete floors where the prevention of dusting, sealing against occasional oil and grease spillages, and an easily cleaned surface is required. Recommended for light industrial use in low traffic areas.

PRODUCT TO USE:

Cementaid "CALRES 120"

HOW TO SPECIFY:

All surfaces to be thoroughly dry and free of all oil and grease. Brush down to remove all surface dust and loose matter. Apply one or two coats of **Cementaid "CALRES 120"**, depending on the porosity of the floor, at the rate of 4-5m² per litre.

Cementaid "CALRES 120" is best applied by brush, short-nap lambswool roller, or knapsack spray. Equipment should be cleaned with solvent based thinners such as Xylol.

EFFECTS:

A clear semi-glaze impregnation which dissolves most types of efflorescence and enhances the natural colour of the concrete. Dust proofs the floor and seals it to resist staining from occasional spillages.

For heavy duty or high wear, exterior applications, or for coloured applications, we recommend you specify and use **Cementaid ROKITE**, or **Cementaid LB9**.

WHERE RECOMMENDED:

All concrete surfaces subject to dusting, where light industrial traffic or wear, or where minor oil and grease spills are expected.

NOTE:

Cementaid "CALRES120" is an acrylic resin in a penetrating solvent, and does NOT contain any silicone resins.

FOR APPLICATION SERVICE:

Contact your local **Cementaid** representative.



Australian owned

INDUSTRIAL FLOOR SPECIFICATIONS • CONCRETE WATERPROOFING & CORROSION-PROOFING ADMIXTURES
OIL & SOLVENT PROOFING • SURFACE TOUGHENING & DUSTPROOFING • ANTI-CORROSION IMPREGNATIONS
RAPID HARDENING • RETARDING • GEL CONTROL AGENT • MORTAR AND DAMPCOURSE ADMIXTURES, etc.

The information and recommendations herein are, as a result of experience and testing, accurate to the best of the seller's knowledge. However, as the proposed use and the circumstances surrounding such use are not known to the seller, it does not guarantee or warrant the product's suitability in any particular instance and shall not be liable for any loss or damage consequent upon any use whatsoever unless the seller has otherwise stipulated the product's suitability for a particular use in writing signed by a Director of the seller.

TECHNICAL SERVICE OFFICES

ADELAIDE

Tel: (08) 8346 9711
Fax: (08) 8346 9977

CEMENTAID (SA & NT) Pty Ltd
ACN: 089 037 749
70 Chief Street
Brompton SA 5007

BRISBANE

Tel: (07) 3276 7388
Fax: (07) 3276 7399

CEMENTAID (QLD) Pty Ltd
ACN: 009 716 018
1/86 Boyland Avenue
Coopers Plains QLD 4108

MELBOURNE

Tel: (03) 9890 0487
Fax: (03) 9890 6223

CEMENTAID (VIC) Pty Ltd
ACN: 004 518 889
15 Clarice Road
Box Hill VIC 3128

PERTH

Tel: (08) 9470 5858
Fax: (08) 9470 5999

CEMENTAID (WA) Pty Ltd
ACN: 000 477 476
200 Star Street
Carlisle WA 6101

SYDNEY

Tel: (02) 9810 0725
Fax: (02) 9810 4164

CEMENTAID (NSW) Pty Ltd
ACN: 000 366 549
44 Alberto Street
Lilyfield NSW 2040

EXPORT SERVICE & PRODUCTION: CEMENTAID International, 80 O'Neill Street, Leichhardt NSW 2040 Tel: (02) 9810 0725 Fax: (02) 9810 4164 www.cementaid.com * Reg. Trade mark