

you can **RELY** on

# CEMENTAID

www.cementaid.com

## SPECIFICATION FOR

# SILICONE & ACRYLIC MASONRY SEALER

# SILICONE S50\*

### REQUIREMENTS:

Surface preservation & protection against moisture penetration (e.g. wind-driven rain, etc) for concrete, block-work, masonry, renders, etc. Long term protection of concrete, brick and stonework against weathering, staining or mould decay, while enhancing natural texture and appearance. Protective surface treatment for all masonry in marine environments. Long term preservation and protection for pre-cast exposed aggregate panels, architectural concrete and masonry.

### PRODUCT TO USE: SILICONE S50

### HOW TO SPECIFY:

All exposed surfaces (specify areas and masonry type) shall be weatherproofed by a single flooded application of **Cementaid SILICONE S50** at manufacturer's recommended coverage rates. All surfaces to be clean and dry before application.

### COVERAGE:

Pressed clay brickwork/pavers	Not less than 1 litre per 5.0 sq. metres
Texture and wire cut bricks	Not less than 1 litre per 3.5 sq. metres
Concrete and cement render	Not less than 1 litre per 3-6 sq. metres
Concrete block	Not less than 1 litre per 2-3 sq. metres
Fibro cement roofing and wall cladding (Natural finish)	Not less than 1 litre per 3.0 sq. metres
Sandstone	Not less than 1 litre per 2.0 sq. metres
Mt Gambier Stone	Not less than 1 litre per 1.5 sq. metres
Terracotta or cement tiles	Not less than 1 litre per 5.0 sq. metres

### EFFECTS:

**SILICONE S50** is a unique combination of Silicones and Acrylic Glazing Liquid. Surfaces treated are not only water repellent but sealed to resist penetration of rain water under wind pressure. **SILICONE S50** in a single application highlights the natural colour of masonry but does not produce a glazed finish. Two applications produces a "wetted" effect and a subdued glaze to dense surfaces such as exposed aggregate concrete panels and roof tiles.

### WHERE RECOMMENDED:

All natural unpainted masonry surfaces.



Australian owned

INDUSTRIAL FLOOR SPECIFICATIONS • CONCRETE WATERPROOFING & CORROSION-PROOFING ADMIXTURES  
OIL & SOLVENT PROOFING • SURFACE TOUGHENING & DUSTPROOFING • ANTI-CORROSION IMPREGNATIONS  
RAPID HARDENING • RETARDING • GEL CONTROL AGENT • MORTAR AND DAMPCOURSE ADMIXTURES, etc.

The information and recommendations herein are, as a result of experience and testing, accurate to the best of the seller's knowledge. However, as the proposed use and the circumstances surrounding such use are not known to the seller, it does not guarantee or warrant the product's suitability in any particular instance and shall not be liable for any loss or damage consequent upon any use whatsoever unless the seller has otherwise stipulated the product's suitability for a particular use in writing signed by a Director of the seller.

### TECHNICAL SERVICE OFFICES

#### ADELAIDE

Tel: (08) 8346 9711  
Fax: (08) 8346 9977

CEMENTAID (SA & NT) Pty Ltd

ACN: 089 037 749  
70 Chief Street  
Brompton SA 5007

#### BRISBANE

Tel: (07) 3276 7388  
Fax: (07) 3276 7399

CEMENTAID (QLD) Pty Ltd

ACN: 009 716 018  
1/86 Boyland Avenue  
Coopers Plains QLD 4108

#### MELBOURNE

Tel: (03) 9890 0487  
Fax: (03) 9890 6223

CEMENTAID (VIC) Pty Ltd

ACN: 004 518 889  
15 Clarice Road  
Box Hill VIC 3128

#### PERTH

Tel: (08) 9470 5858  
Fax: (08) 9470 5999

CEMENTAID (WA) Pty Ltd

ACN: 000 477 476  
200 Star Street  
Carlisle WA 6101

#### SYDNEY

Tel: (02) 9810 0725  
Fax: (02) 9810 4164

CEMENTAID (NSW) Pty Ltd

ACN: 000 366 549  
44 Alberto Street  
Lilyfield NSW 2040

EXPORT SERVICE & PRODUCTION: CEMENTAID International, 80 O'Neill Street, Leichhardt NSW 2040 Tel: (02) 9810 0725 Fax: (02) 9810 4164 www.cementaid.com \* Reg. Trade mark