

you can **RELY** on



www.cementaid.com

SPECIFICATION FOR

“WET LOOK” SEALER FOR SLATE

SLATE SEALER

REQUIREMENT:

A clear, mid-gloss protective surface treatment used for all slate surfaces, both walls and floors. Also suitable for use with terracotta (indoors) and clay tiles or other dense masonry.

Protects the surface from wear caused by foot traffic, and from staining by spillages. Enhances and beautifies the appearance of the slate by imparting a “Wet Look” to the surface.

PRODUCT TO USE:

Cementaid SLATE SEALER

HOW TO SPECIFY:

“All surfaces to be thoroughly clean, dry and free of loose material. Apply by brush, short nap lambswool roller or low pressure spray, two (2) coats of **SLATE SEALER**, allowing 4-6 hours between coats, at the rate of approx. 1 litre per 8-12 square metres. Recoat or touch-up within 48 hours of initial application.

EFFECTS:

A clear acrylic sealer which brings out the natural colour of slate, clay and terracotta tiles, without imparting a high gloss finish. Fully washable, using a mild aqueous detergent (do not use harsh detergents, solvents, or abrasives to clean **SLATE SEALER**).

Note: Not recommended for use with terracotta tiles outdoors – use **Cementaid DRIWAL P6** or **Cementaid Silicone S50** for this application.

NON-SLIP: Also available in a non-slip formulation.

WHERE RECOMMENDED:

All slate surfaces, both walls and floors. Also suitable for use with terracotta (indoors) and clay tiles.

CAUTION:

SLATE SEALER is flammable.
NO SMOKING. NO NAKED FLAMES.

Observe all usual precautions with solvents.

Use only under well ventilated conditions.

Refer to Material Safety Data Sheet for **Slate Sealer**. **Do not use** in areas where solvent odours may enter building ventilation air intakes or adjacent structures, or affect stored foodstuffs or other material.



FOR APPLICATION SERVICE:

CONTACT CEMENTAID FOR SUPPLY AND APPLICATION SERVICE



Australian owned

INDUSTRIAL FLOOR SPECIFICATIONS • CONCRETE WATERPROOFING & CORROSION-PROOFING ADMIXTURES
OIL & SOLVENT PROOFING • SURFACE TOUGHENING & DUSTPROOFING • ANTI-CORROSION IMPREGNATIONS
RAPID HARDENING • RETARDING • GEL CONTROL AGENT • MORTAR AND DAMPCOURSE ADMIXTURES, etc.

The information and recommendations herein are, as a result of experience and testing, accurate to the best of the seller's knowledge. However, as the proposed use and the circumstances surrounding such use are not known to the seller, it does not guarantee or warrant the product's suitability in any particular instance and shall not be liable for any loss or damage consequent upon any use whatsoever unless the seller has otherwise stipulated the product's suitability for a particular use in writing signed by a Director of the seller.

TECHNICAL SERVICE OFFICES

ADELAIDE

Tel: (08) 8346 9711
Fax: (08) 8346 9977

CEMENTAID (SA & NT) Pty Ltd
ACN: 089 037 749
70 Chief Street
Brompton SA 5007

BRISBANE

Tel: (07) 3276 7388
Fax: (07) 3276 7399

CEMENTAID (QLD) Pty Ltd
ACN: 009 716 018
1/86 Boyland Avenue
Coopers Plains QLD 4108

MELBOURNE

Tel: (03) 9890 0487
Fax: (03) 9890 6223

CEMENTAID (VIC) Pty Ltd
ACN: 004 518 889
15 Clarice Road
Box Hill VIC 3128

PERTH

Tel: (08) 9470 5858
Fax: (08) 9470 5999

CEMENTAID (WA) Pty Ltd
ACN: 000 477 476
200 Star Street
Carlisle WA 6101

SYDNEY

Tel: (02) 9810 0725
Fax: (02) 9810 4164

CEMENTAID (NSW) Pty Ltd
ACN: 000 366 549
44 Alberto Street
Lilyfield NSW 2040