

you can **RELY** on



www.cementaid.com

## SPECIFICATION FOR

# MORTAR COLOUR (BROWN)

# MORTABROWN\*

### REQUIREMENT:

Brown mortar colour for all external brickwork mortar and for internal feature walls.

### PRODUCT TO USE:

### Cementaid MORTABROWN

### HOW TO SPECIFY:

All mortar (state areas) shall be made brown coloured by the addition of **Cementaid MORTABROWN** at a rate of not less than 2 litres for each 40Kg bag of cement used in the mix. No lime shall be used in coloured mortar.

### EFFECTS:

Produces a dense, **BROWN** mortar for masonry, renders, toppings, etc. **MORTABROWN** contains ingredients which greatly reduce efflorescence on bricks and mortar. As with all mortar colours the mortar must be struck back from the brick face or rodded hard to bring cement to surface.

### WHERE RECOMMENDED:

All masonry construction where a coloured mortar effect is desired. **MORTABROWN** is suitable for colouring screeds, renders, toppings and concrete at the above dose rate.

### PACKAGING:

205 Litre, 20 Litre, 5 Litre, 1 Litre

### NOTE:

### STIR WELL BEFORE USE

Not to be used as a brown damp course. When exposed to UV light & weathering (e.g. exterior), the coloured effect produced by **Cementaid MORTABROWN** is subject to fading over time. To minimise UV exposure, coloured mortars should be struck back from the brick surface and/or rodded hard to bring cement to the surface.



Australian owned

INDUSTRIAL FLOOR SPECIFICATIONS • CONCRETE WATERPROOFING & CORROSION-PROOFING ADMIXTURES  
OIL & SOLVENT PROOFING • SURFACE TOUGHENING & DUSTPROOFING • ANTI-CORROSION IMPREGNATIONS  
RAPID HARDENING • RETARDING • GEL CONTROL AGENT • MORTAR AND DAMPCOURSE ADMIXTURES, etc.

The information and recommendations herein are, as a result of experience and testing, accurate to the best of the seller's knowledge. However, as the proposed use and the circumstances surrounding such use are not known to the seller, it does not guarantee or warrant the product's suitability in any particular instance and shall not be liable for any loss or damage consequent upon any use whatsoever unless the seller has otherwise stipulated the product's suitability for a particular use in writing signed by a Director of the seller.

### TECHNICAL SERVICE OFFICES

#### ADELAIDE

Tel: (08) 8346 9711

Fax: (08) 8346 9977

CEMENTAID (SA & NT) Pty Ltd

ACN: 089 037 749

70 Chief Street

Brompton SA 5007

#### BRISBANE

Tel: (07) 3276 7388

Fax: (07) 3276 7399

CEMENTAID (QLD) Pty Ltd

ACN: 009 716 018

1/86 Boyland Avenue

Coopers Plains QLD 4108

#### MELBOURNE

Tel: (03) 9890 0487

Fax: (03) 9890 6223

CEMENTAID (VIC) Pty Ltd

ACN: 004 518 889

15 Clarice Road

Box Hill VIC 3128

#### PERTH

Tel: (08) 9470 5858

Fax: (08) 9470 5999

CEMENTAID (WA) Pty Ltd

ACN: 000 477 476

200 Star Street

Carlisle WA 6101

#### SYDNEY

Tel: (02) 9810 0725

Fax: (02) 9810 4164

CEMENTAID (NSW) Pty Ltd

ACN: 000 366 549

44 Alberto Street

Lilyfield NSW 2040

EXPORT SERVICE & PRODUCTION: CEMENTAID International, 80 O'Neill Street, Leichhardt NSW 2040 Tel: (02) 9810 0725 Fax: (02) 9810 4164 www.cementaid.com

\* Reg. Trade mark