

you can **RELY** on

CEMENTAID

www.cementaid.com

SPECIFICATION FOR

ACID – BASED CLEANER FOR BRICKS, BLOCKS AND CONCRETE

BRICKCLEANER *

REQUIREMENT:

Easy cleaning & removal of mortar stains and dirt from masonry walls, floors, tools etc, without affecting the surfaces being cleaned. Formulated from a blend of acids, **Cementaid BRICKCLEANER** will also remove grease and soap deposits from tiles in showers and bathrooms. Can also be used for light acid etch of concrete floors, prior to application of surface coatings.

PRODUCT TO USE:

Cementaid BRICKCLEANER

HOW TO SPECIFY:

Remove excess mortar, dirt & grease with scraper or stiff brush to save time & material. All areas shall be pre-wetted with water and cleaned using **Cementaid BRICKCLEANER** diluted with clean water in the ratio 4 parts water:1 part Brickcleaner, applied copiously and worked well into surface by the use of a scrubbing brush, broom or wire brush to facilitate removal of heavy soiling. Leave for up to 3 minutes then wash off with plenty of clean cold water.

EFFECTS:

BRICKCLEANER reacts with the cement particles, or with the dirt/brick interface, to dissolve the soiling and facilitate it's removal using high pressure water. May be diluted as above for normal use, or used "neat" if required for heavy soiling.

WHERE RECOMMENDED:

BRICKCLEANER can be applied to most Brick, Block or Concrete surfaces that have been soiled. It is recommended to apply a test area first as the density of the surface can produce different results.

PACKAGING:

205 Litre, 20 Litre, 5 Litre, 1 Litre

CAUTION:



Cementaid BRICKCLEANER is a corrosive product. Wear protective gloves / goggles / clothing, etc. Refer to Material Safety Data Sheet (MSDS) for safety, protection, cleaning and washing instructions.

NOTE:

Do not leave **Brickcleaner** in contact with the surface for more than 3 minutes, before hosing off with clean water in order to ensure that only the contaminants are removed and not the surface itself. Application to a small trial area is recommended to determine optimum period before hosing-off. Collect any run-off & neutralise using alkali prior to disposal.



Australian owned

INDUSTRIAL FLOOR SPECIFICATIONS • CONCRETE WATERPROOFING & CORROSION-PROOFING ADMIXTURES
OIL & SOLVENT PROOFING • SURFACE TOUGHENING & DUSTPROOFING • ANTI-CORROSION IMPREGNATIONS
RAPID HARDENING • RETARDING • GEL CONTROL AGENT • MORTAR AND DAMPCOURSE ADMIXTURES, etc.

The information and recommendations herein are, as a result of experience and testing, accurate to the best of the seller's knowledge. However, as the proposed use and the circumstances surrounding such use are not known to the seller, it does not guarantee or warrant the product's suitability in any particular instance and shall not be liable for any loss or damage consequent upon any use whatsoever unless the seller has otherwise stipulated the product's suitability for a particular use in writing signed by a Director of the seller.

TECHNICAL SERVICE OFFICES

ADELAIDE

Tel: (08) 8346 9711
Fax: (08) 8346 9977

CEMENTAID (SA & NT) Pty Ltd

ACN: 089 037 749
70 Chief Street
Brompton SA 5007

BRISBANE

Tel: (07) 3276 7388
Fax: (07) 3276 7399

CEMENTAID (QLD) Pty Ltd

ACN: 009 716 018
1/86 Boyland Avenue
Coopers Plains QLD 4108

MELBOURNE

Tel: (03) 9890 0487
Fax: (03) 9890 6223

CEMENTAID (VIC) Pty Ltd

ACN: 004 518 889
15 Clarice Road
Box Hill VIC 3128

PERTH

Tel: (08) 9470 5858
Fax: (08) 9470 5999

CEMENTAID (WA) Pty Ltd

ACN: 000 477 476
200 Star Street
Carlisle WA 6101

SYDNEY

Tel: (02) 9810 0725
Fax: (02) 9810 4164

CEMENTAID (NSW) Pty Ltd

ACN: 000 366 549
44 Alberto Street
Lilyfield NSW 2040

EXPORT SERVICE & PRODUCTION: CEMENTAID International, 80 O'Neill Street, Leichhardt NSW 2040 Tel: (02) 9810 0725 Fax: (02) 9810 4164 www.cementaid.com * Reg. Trade mark